SEISURE TIME

SIMPLE SPA CARE PROGRAM

Start-Up

- Polish the entire spa surface with Fast Gloss prior to filling.
- Add Metal Gon during the fill cycle.
- Balance water according to your Leisure Time dealer's instructions, or if you use Spa & Hot Tub Test Strips to test water, plug in the results using the online water analysis at LeisureTimeSpa.com for corrective action.
- By adding pH Balance Plus* at this time, you will reduce the need to adjust your pH for up to three months.
- Add any Leisure Time sanitizer.**
- Test water using Spa & Hot Tub Test Strips to make sure water is still balanced.
- Shock with Renew or Renew Tabs. Skip this step if using Reserve & Renew sanitizing system.

*pH Balance Plus is sold individually at your local spa retailer.
**See Spa Care Guide for Leisure Time's sanitizer choices.

Weekly

Always allow product to circulate in water for one minute with jets on prior to adding another product. Circulate water for 10 minutes after all products are added.

- Test water using Spa & Hot Tub Test Strips from Leisure Time. Adjust as needed.
- 2 Add *Bright & Clear* according to label directions.
- **3** Add *Defender* according to label directions.
- ♠ Add Enzyme according to label directions.
- Add Renew or Renew Tabs to shock water according to label directions.

After Each Use

Shocking with *Renew* or *Renew Tabs* after each use is suggested. Shocking with *Renew or Renew Tabs* is required if using the *Reserve & Renew** System.

Monthly Cleaning

- Remove the spa filter and clean using *Instant Cartridge Clean*.
- Spa cover should be cleaned using either Cover Wipes or Cover Care & Conditioner.

3-Month Cleaning

- Add Jet Clean according to label directions. (Remember to remove filter prior to use.)
- Orain your spa.
- Clean the shell of the spa with CitraBright and wipe down.
- Apply Fast Gloss to spa surface to protect, seal and keep the spa finish from fading.
- **5** Deep clean filter with *Filter Clean*.
- Follow Start-Up procedure including having your source water tested professionally.
- Replace your Spa Mineral Purifier.
- Clean your spa cover with Cover Wipes or Cover Care & Conditioner.

Prior to each use, test spa water to ensure that sanitizer level is in proper range of 3-5 ppm.

If spa is used more than three times per week, water testing and maintenance will need to be performed more frequently.

Filter cycle should be run a minimum of 6-8 hours per day.

To ensure water quality and keep the water easy to balance, Leisure Time recommends draining your spa water at least every three months, or more often if the spa is used frequently.

PROPER LEVELS FOR BALANCED WATER

TOR DALANCED WATE		
pН	7.2 - 7.8	
Alkalinity	80 - 120 ppm	
Calcium Hardness	150 – 400 ppm	
Sanitizer	3 – 5 ppm	

This program is intended for a residential spa with average use. It is not designed for public, commercial or semi-public spas. If your spa is used more than 3 times per week, you should check and make chemical additions more often than suggested.



TROUBLESHOOTING COMMON PROBLEMS

Problem	Cause	Solution
	Excessive organic contaminants or lack of sanitizer	Shock with <i>Renew</i> or <i>Renew Tabs</i> . Check and adjust sanitizer level.
	Buildup of unfilterable material	Use Bright & Clear.
Cloudy Water	pH or total alkalinity out of balance	Test water and adjust pH and total alkalinity as necessary using <i>Spa Up, Spa Down</i> or <i>Alkalinity Increaser.</i>
	Dirty filter	Use <i>Instant Cartridge Clean</i> on a monthly basis, or use <i>Filter Clean</i> for deep cleaning.
	Calcium too high	Use <i>Defender</i> on a weekly basis.
Chalky, white		Han Dafan dan an a sua abbubania
scale deposits	High mineral content in water	Use <i>Defender</i> on a weekly basis.
(Calcium buildup)	Water out of balance	Check water balance and adjust as necessary.
Cloudy green	Low sanitizer level	Shock with <i>Renew</i> or <i>Renew Tabs</i> .
water		Check and adjust sanitizer level.
Clear green water	Dissolved copper or iron in spa water	Add <i>Metal Gon</i> to sequester minerals in the water. Check pH level.
Brown water	High iron or manganese content	Add <i>Metal Gon</i> to sequester minerals in the water. Check pH level.
Odor	Excessive organic contaminants	Shock with <i>Renew</i> or <i>Renew Tabs</i> . Check and adjust sanitizer level.
Eye/skin	Chloramines or excessive organic contaminants	Shock with <i>Renew</i> or <i>Renew Tabs</i> .
irritation	pH or total alkalinity out of balance	Test and adjust pH and total alkalinity as necessary.
Scum deposit on waterline	Oils, lotions and detergents from bathers have caused buildup	Use <i>Enzyme</i> on a weekly basis.
Excessive	Buildup of body oils, cosmetics and detergents from bathers	Add Foam Down. Shock with Renew or Renew Tabs.
foaming	Calcium Hardness is too low	Add <i>Calcium Booster</i> to obtain 150–400 ppm calcium level in the water.
	Large amount of Total Dissolved Solids	Change water.